



OPERATING INSTRUCTION

powerCON® TRUE1 TOP | Cable Connector

1. CONNECTING



Note:
When connecting, match the notch on the cable connector to the corresponding guide slot on the chassis.



SAFETY WARNING

incorrect insertion may cause electrical contact misalignment resulting in equipment malfunction and/or personal injury.



Note:
After inserting properly as in illustration **A**, twist the cable connector clockwise to lock.



click



Note:
The proper twist-lock is achieved when the silvery tab is in the position shown in **C** and an audibel «click» is heard.



2. UNLOCKING



3. APPLICATION INSTRUCTION

Application other equipment:

- The powerCON® TRUE1® system is certified as a connector with breaking capacity according IEC 60320, VDE 0625.
- It is intended for use as an appliance coupler and interconnection coupler.
- It serves to supply power to an appliance and from an appliance to other equipment.
- To be installed by qualified person only.

CONNECTOR ASSIGNMENT:

APPLIANCE INLET

NAC3MPX-TOP
NAC3MPX-WOT-TOP

Power IN ▶



NAC3FX-W-TOP
(Connector)

NAC3MX-W-TOP
(Plug connector)

APPLIANCE OUTLET

NAC3FPX-TOP
NAC3FPX-WOT-TOP
NAC3FPX-ST-TOP

Power OUT ◀



NAC3FX-W-TOP
(Connector)

NAC3MX-W-TOP
(Plug connector)

APPLIANCE INLET / OUTLET

▶ Combination

NAC3PX-TOP

Power IN ▶



Power OUT ◀

powerCON® TRUE1® TOP line is full backward compatible with the preceding powerCON TRUE1 products.

Approval based:	VDE EN 60320-1	UL 60320-1 CAN/CSA-C22.2 No. 60320-1
Rating:	250 V ac / 16 A	250 V ac / 20 A
Cable Type:	H05VV-F3G 1.0 mm ² , Length max. 2 m H05VV-F3G 1.5 - 2.5 mm ² H07RN-F3G 1.5 mm ²	SJTOW, SJOOW 3 x 12 AWG
Cable O.D.:	6.0 - 12.0 mm	6.0 - 12.0 mm

The manufacturer of cord sets and of interconnection cord sets is responsible for the conformity assessment according to the applicable regulatory documents.



Draft. Nr.: BDA 556 V3
Update: 2023-06-28

Neutrik AG | LI-9494 Schaan
www.neutrik.com

Data subject to change without prior notice. © 2023 NEUTRIK®. NEUTRIK®, powerCON are registered trademark of Neutrik AG. ALL RIGHTS RESERVED.