



Ref. Certif. No.

SE-105346M1

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product	Connectors
Name and address of the applicant	NEUTRIK AG Im alten Riet 143 9494 Schaan LIECHTENSTEIN
Name and address of the manufacturer	Same as applicant
Name and address of the factory	Same as applicant
Note: When more than one factory, please report on page 2	
Ratings and principal characteristics	50V AC, 16A, IP40
Trademark / Brand (if any)	NEUTRIK or 
Customer's Testing Facility (CTF) Stage used	-
Model / Type Ref.	See page 2
Additional information (if necessary may also be reported on page 2)	<input checked="" type="checkbox"/> Additional Information on page 2
A sample of the product was tested and found to be in conformity with	IEC 61984:2008
As shown in the Test Report Ref. No. which forms part of this Certificate	2306399STO-001

This CB Test Certificate is issued by the National Certification Body

Intertek Semko AB
Torshamnsgatan 43
Box 1103
SE-164 22 Kista, Sweden

Date: 13 December, 2023

intertek

Signature:

Fredrik Wennersten

Model / Type Ref.

NC3FXX-BAG-MC, NC3FXX-GP, NC3FXX, NC3FXX-14-BAG, NC3FXX-14, NC3FXX-BAG, NC3FXX-BAG-WOB, NC3FXX-WOB, NC3FXX-WT, NC3FXX-BSC-DOM, NC3FXX-AU-WOP, NC3FXX-B-H, NC3FXX-B-M, NC3FXX-14-B, NC3FXX-B, NC3FXX-B-CRYSTAL, NC3MXX-14-LES, NC3MXX-BAG-MC, NC3MXX-B-H, NC3MXX-GP, NC3MXX, NC3MXX-14-BAG, NC3MXX-BAG, NC3MXX-BAG-WOB, NC3MXX-WOB, NC3MXX-WT, NC3MXX-HE, NC3MXX-BSC-DOM, NC3MXX-EMC-HESOM, NC3MXX-B-M, NC3MXX-14-B, NC3MXX-14, NC3MXX-AU-WOP, NC3MXX-B, NC3MXX-B-CRYSTAL, NC3MXX-B-WOB

Additional information

This certificate replaces previously issued ref. No SE-105346 dated 3 August 2021. A new certificate has been issued due to alternative material of insert added.

Any type designations may be added with "-D" as an indicator of a packaging variant.

Additional information:

Cable connectors with solder terminals for use with audio applications. COC and without interlock. PTI: 175. Pollution degree 2. IP40, OVC I and Uimp 1500V. Max conductor area 2,5mm².

Additional flammability information:

Type	Part	Material	Thickness	Flammability
NC3M* NC3F* Connectors	Inserts	PA66	0,4 – 2,0 mm	V-0 UL 94

Date: 13 December, 2023

Signature:

