



NA3FJ

三芯XLR母 -1/4"立体声带锁插口(尖端，环，套管接触)

特征和性能

- 多功能的，预配的，可靠地锁定不同的链接系统
- 专业的外观和紧凑小巧的设计，基于XX系列
- 坚固的压铸外壳提供最好的可靠性

Technical Information

| Product | |
|-----------------|---------|
| Title | NA3FJ |
| Connection Type | Adapter |

| Electrical | |
|-----------------------|---------------------------------|
| Contact resistance | $\leq 3 \text{ m}\Omega$ (XLR) |
| Contact resistance | $\leq 6 \text{ m}\Omega$ |
| Dielectric strength | 1.5 kV dc / > 1 kVdc (XLR/Jack) |
| Insulation resistance | > 2 G Ω |

| Mechanical | |
|----------------|------------|
| Wiresize | |
| Locking device | Latch lock |

| Material | |
|-----------------|----------------------------|
| Contact plating | 2 μm Ag |
| Contacts | Bronze (CuBe2) (jack) |
| Insert | Polyamide (PA 6.6 30 % GR) |
| Shell | Zinc diecast (ZnAl4Cu1) |
| Shell plating | gal Cu/Ni |

| Environmental | |
|-------------------|------------------|
| Temperature range | -20 °C to +65 °C |