



NC3FX-BAG

镀黑金属外壳和镀银触点的3芯母头电缆连接器

公认的XLR连接器标准，4个零件以及无任何螺丝保证快速安装，紧凑的设计和坚固的压铸外壳，玻璃纤维材料成就结实的塑料内芯，卡盘式夹线套确保所有的电缆线夹紧。

特征和性能

- 坚固的锌压铸外壳，长效，可靠
- 橡胶密封的尾套给电缆的弯曲应力提供更周到的保护
- 符合UL认证的零部件
- 卡盘式夹线套确保所有的电缆线夹紧
- 提供编码或标识的彩色环及尾套

Technical Information

Product	
Title	NC3FX-BAG
Connection Type	XLR
Gender	female

Electrical	
Capacitance between contacts	≤ 4 pF
Contact resistance	≤ 3 m Ω
Dielectric strength	1,5 kVdc
Insulation resistance	> 10 G Ω (initial)
Rated current per contact	16 A
Rated voltage	< 50 V

Mechanical	
Cable O.D.	3.5 - 8.0 mm
Insertion force	≤ 20 N
Withdrawal force	≤ 20 N
Lifetime	> 1000 mating cycles
Wiresize	max. 2.5 mm ²
Wiresize	max. 14 AWG
Wiring	Solder contacts
Locking device	Latch lock

Material	
Boot	Polyurethan
Contact plating	2 µm Ag over 2 µm Ni
Contacts	Bronze (CuSn8)
Insert	Polyamide (PA66)
Locking element	St3K32 (latch) / Ck 67 (spring)
Shell	Zinc diecast (ZnAl4Cu1)
Shell plating	Black chromium
Strain relief	Polyacetal (POM)

Environmental	
Approvals	UL
Flammability	UL 94 V-0
Standard compliance	IEC 61076-2-103
Protection class	IP 40
Solderability	Complies with IEC 68-2-20
Temperature range	-30 °C to +80 °C